



Low Pitch Roof Window System

Roof Window System for installation at pitches below 15°

Window Specifications

Window Size	550mm x 980mm
Glazing Size	370mm x 825mm
Window U-Value	1.4 W/m ² K
Glazing U-Value	1.1 W/m ² K
RW Coefficient	32 dB
Finishes Available	White / Pine

Forticrete low pitch roof window system has been specifically designed to be installed with Centurion tiles on roof pitches under 15°. The system consists of two large drainage panels fixed beneath the tiling battens and window flashings which completely protect the area directly surrounding the roof window. As experienced roofing specialists we realise that detailing is critical at a low pitch. Our team of experts developed this system to ensure that the junctions around the roof window are always fully protected. For more information on how the system works, please visit our website and follow the link to our installation video.

Key Considerations

- Maximum rafter length 5m
- Minimum rafter length 2.5m
- Single storey buildings only
- Sheltered locations only
- Roof pitches from 10-15°
- One window size only
- All Centurion limitations apply (refer to Centurion literature)

For an estimate (simple rectangular lean-to roof shapes) including Forticrete Centurion roof tiles, simply contact our Customer Services office on 01525 244900 and provide the eave length, rafter length, and number of windows required.

When installed in accordance with our full installation guide with Forticrete Centurion roof tiles, this system carries a 10 year guarantee.

For more information please visit www.forticrete.co.uk/lowpitch



Low Pitch System Contents

LPS Box

- Roof Window
- Flashings
- Pitching Kerb
- Brackets + Fixings

Tray Pack

- Bottom Tray
- Top Tray
- Sealing Tape (2m)
- Foam Support Blocks
- 45mm Screws + Washers
- Tile Adhesive

Eaves Pack (3m)

- Underlay Support Tray
- Eaves Batten Blocks
- Eaves Filler Clips
- Eaves Filler Clip Screws 45mm
- Eaves Filler Clip Screws 80mm
- Eaves Batten

Abutment Pack (3m)

- Centurion Top Fillers
- Felt Spacers
- Top Filler Clips

When ordered with Centurion tiles the following will be included:

- Centurion Tiles
- Verge Tiles
- Tile Clips
- Verge Clips

Note - Tiling Battens, Underlay, Screws & Nails for battens are not included.

Frequently Asked Questions

What is the minimum spacing between two windows?	Minimum 1800mm between window centres, battens must have 3 fixings into rafters between trays.
Can I use your trays with another window?	No, the flashings have been specifically designed to fit with the Forticrete tray.
Can I buy the window through another supplier?	No, the complete system is supplied by Forticrete. The system can be ordered through Centurion Tile stockists, for more information please contact our customer service department.
Can I order the system without Centurion tiles?	Yes. Forticrete are unable to guarantee the system without the installation of Centurion tiles.
Do you offer other sizes?	Not at the moment, we may look to expand the range in the future.

Roofing Systems & Technical enquiries:

Forticrete Limited,
Boss Avenue, off Grovebury Road,
Leighton Buzzard, Beds LU7 4SD
Tel: 01525 244900
Fax: 01525 850432
E-mail: roofingtechnical@forticrete.com

Information on the complete range of Forticrete products can be found on the Internet at www.forticrete.co.uk

Forticrete, Gemini, Minislate, Centurion, Senator, V2, Hardrow Slates, Ecotile, Ecotile Plus and Ecoslate logo's are registered trademarks of Forticrete Ltd.

Component designs in this literature are registered in Europe

The information contained within this publication is as accurate as possible at the time of going to press. However, this document does not form part of any contract and Forticrete cannot accept liability for any errors or omissions.

In order to maintain its position as a market leader, Forticrete operates a policy of continuous product development and therefore reserves the right to alter specifications without notice.

© Forticrete Ltd. 2017

